

Details**Processor**

Intel Pentium III 600Mhz clock speed with Speedstep Technology
 100MHz bus speed
 32KB write back Level 1 cache
 256KB Level 2 cache Memory (std/max RAM) 64MB/512MB 100MHz SDRAM Hard Disk
 6.0 billion bytes (5.6GB) unformatted capacity Floppy Drive, CD-ROM & DVD-ROM
 Floppy Drive: External / internal swappable 3.5" 1.44MB
 CD-ROM: Twenty-four speed (max) internal swappable Graphics
 S3 Savage MX 64 Bit AGP, 8MB SGRAM, BitBLT graphics processor Display
 High resolution Thin Film Transistor (TFT) colour LCD (1024 x 768 pixel resolution)
 Up to 16.7 million colours
 13.3" (33.8cm) diagonal display size

Keyboard

86 full size keys including embedded numeric keypad, 12 function keys, 8 hot keys, 2 Windows keys and Euro key
 New Accupoint II integrated pointing device with scroll up/down buttons Interfaces/Expansion Slots
 ECP parallel port, Serial port (16550 UART equivalent)
 SVGA monitor port
 PS/2 keyboard/mouse port
 IrDA V1.1 infra-red port
 USB port
 RJ11 modem interface
 2 x PC Card Type II or 1 x PC Card Type III (CardBus supported)
 Memory expansion slot
 Headphone socket, External microphone socket
 NTSC / PAL video output
 External floppy disk port
 SelectBay for swappable Floppy / CD-ROM / DVD-ROM [Note: Windows NT4.0 does not support DVD Video] / extra battery /
 Zip drive / LS120 options
 Proprietary docking connector for NetDock modular docking system, or CardDock
 Additional expansion options through docking solution and SelectBay Dimensions (W x D x H) & Weight
 312 x 254 x 36mm
 2.6 kg with CD Power Supply
 Autosensing AC Adaptor (100/240v) for worldwide usage Battery
 Rechargeable, removable lithium-ion battery
 3-4hrs hours per charge (up to 7 hours with optional secondary SelectBay battery) Special Features
 16 Bit sound system supports SoundBlaster Pro format; Built-in stereo speakers
 Integrated V.90 56k modem
 APM/ACPI support; Power management extensions
 Plug'n' Play BIOS
 SM (DMI) BIOS 2.3
 WfM compliant
 2-level system password, HDD password (via separate s/w utility); Keyboard lock, Screen blank functions
 Fitting for Kensington cable lock
 Power switch lock Warranty Period
 Three year UK and International Bundled Software
 Windows® NT 4.0 or Windows® 2000 (Dual Boot - one time choice*)
 Video Driver, Sound system software, Online manuals
 PC Card and InfraRed software for Windows NT
 Options

32MB, 64MB, 128MB or 256MB (availability tbc) memory upgrade modules (Note: requires 100MHz memory)
 NetDock Port Replicator
 Expansion Station
 CardDock
 SelectBay HDD II Adaptor
 SelectBay options (including CD-ROM Drive, DVD-ROM Drive, Zip drive, Battery, Hard disk, LS120 options)
 PC Card Options
 Spare AC Adapter
 Spare Lithium Ion battery pack
 Battery charger
 Range of networking options
 Deskbased accessories
 Carry cases Video Modes
 Internal:
 640 x 480 x 16.7 million colours
 800 x 600 x 16.7 million colours
 1024 x 768 x 16.7 million colours
 1280 x 1024 x 16.7 million colours (virtual display)
 1600 x 1200 x 65,536 colours (virtual display)

External:

640 x 480 x 16.7 million colours @ 85Hz NI refresh rate
800 x 600 x 16.7 million colours @ 85Hz NI refresh rate
1024 x 768 x 16.7 million colours @ 85Hz NI refresh rate
1280 x 1024 x 16.7 million colours @ 60Hz NI refresh rate
1600 x 1200 x 65,536 colours @ 60Hz NI refresh rate

Simultaneous:

The maximum "non-panning" resolution of each product can be displayed simultaneously on the LCD and on an external monitor, at 60Hz NI

* Please note: From two MS operating systems ("OS") pre-installed you can choose only one by one-time selection. If you desire the rejected OS after you made your selection you need to acquire and pay for such OS as a separate transaction.

** Microsoft and Windows® 2000 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

** Microsoft and Windows NT® 4.0 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.