

Details**Processor**

Intel Pentium II

300MHz clock speed

32KB write back level 1 cache

512KB write through level 2 cache Memory (std/max RAM) 64MB SDRAM standard (expandable to 256MB SDRAM) LIM EMS/XMS supported

Dimensions

311mm x 42mm x 254mm Weight

2.85kg CD-ROM

Swappable internal twenty-four speed (max.) 5.25" Enhanced IDE

(150ms average random access time) DVD-ROM

Optional Module.

NB MPEGII hardware required for decoding Hard Disk

6GB (13ms average access time)

Diskette Drive

Swappable internal 3.5" 1.44MB Graphics

NeoMagic MagicMedia 256AV chipset

VGA/SVGA compatible

2.5MB VRAM

PCI Local Bus support

BitBlock graphics accelerator Display

13.1" diagonal display size

1024 x 768 pixel resolution

High resolution advanced TFT colour LCD up to 16.7 million colours, simultaneous internal/external display mode Video Modes

TV Mode:

640x480, 256 colours,60Hz NTSC, 50Hz PAL

800x600, 256 colours,60Hz NTSC, 50Hz PAL

1024x768, 256 colours,60Hz NTSC, 50Hz PAL

Internal Display:

640x480, 256 colours

640x480, 65,536 colours

640x480, 16.7 million colours

800x600, 256 colours

800x600, 65,536 colours

800x600, 16.7 million colours

1024x768, 256 colours

1024x768, 65,536 colours

1024x768, 16.7 million colours

Simultaneous Display:

640x480, 256 colours @60Hz NI

640x480, 65,536 colours @60Hz NI

640x480, 16.7 million colours @60Hz NI

800x600, 256 colours @60Hz NI

800x600, 65,536 colours @60Hz NI

800x600, 16.7 million colours @60Hz NI

1024x768, 256 colours @60Hz NI

1024x768, 65,536 colours @60Hz NI

1024x768, 16.7 million colours @60Hz NI

External Display:

640x480, 256 colours @85Hz NI

640x480, 65,536 colours @85Hz NI

640x480, 16.7 million colours @85Hz NI

800x600, 256 colours @85Hz NI

800x600, 65,536 colours @85Hz NI

800x600, 16.7 million colours @85Hz NI

1024x768, 256 colours @85Hz NI

1024x768, 65,536 colours @85Hz NI

1024x768, 16.7 million colours @85Hz NI

1280x1024, 256 colours @60Hz NI

Keyboard

Ergonomically designed

86 full size keys with integrated mousepoint

12 function keys, 8 hot keys and 2 W95 keys.

Embedded numeric keypad

Dedicated cursor control keys Interfaces/Expansion Slots
ECP parallel port
RS-232C serial port (16550UART)
Serial infrared port (IrDA V 1.1 Compliant)
SVGA monitor port
2 x 32bit CardBus PC Card slots, (2 x Type II or 1 x Type III)
cardbus enabled
Microphone/Speaker sockets
2 x Toshiba internal memory slot
USB port
PS/2 keyboard/mouse port
ext FDD port
NTSC/PAL out port
240 pin docking port (CSIII with adaptor, CSII and DSV+) Power Supply
Autosensing AC adaptor
100/240v for world-wide usage Battery
Rechargeable removable Li-ion battery
Up to 4.0 hours battery life Software Included
Windows 95 Windows 98 Dual Boot
PC Card support software
SVGA video driver
Sound system software
Infrared file transfer software
On-line manual Hardware Included
Plug and Play BIOS Other Special Features
Two level password security
Auto-resume mode
Toshiba Max Time Power Management
Kensington Cable lock provision
ACPI support
PC98 qualified
LDCM 3.3 bundled
wfw Compliant Options
32MB, 64MB, EDO RAM expansion
CardStation II &III (via adaptor) / Deskstation Vplus
CardStation adaptor
NetworkDock
DeskStation Vplus SelectBay adaptor
SelectBay Options
MPEG II H/W decoding module (Reseller Fit only)
PC Card Options
Spare AC adaptor
Li-ion battery pack
Battery charger
A range of networking options, deskbased accessories and carry cases Remarks